

716054

FR48FE7

FREESTANDING DOUBLE TANK 8+8L ELECTRIC FRYER WITH A WITH IN-TANK ROTATING HEATING ELEMENTS ON CLOSED CABINET - BASKETS, LIDS AND OIL DRAINING TANK INCLUDED



- Freestanding electric fryer 8+8 L with 2 independent tanks on a closed cabinet (40 cm). This space-efficient solution enables the use of 2 types of oil or 2 cooking processes simultaneously within a 1/2 module.
- Power: 2x7 kW.
- Heating through AISI 304 stainless steel rotating armoured heating elements for easy cleaning of the tank and worktop.
- Basket support fixed to the worktop rear.
- Draining on the tank bottom.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- Tank with a filter for collecting oil inside the cabinet, baskets and lids included.
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Deep drawn worktop with a seamlessly welded AISI 304 deep drawn cooking tank, featuring rounded corners.
- Rounded internal profile of the tank to facilitate cleaning, complying with hygiene standards.
- Large front basin and front zone for oil and foam expansion.
- Adjustable operating thermostat ranging between 100°C and 190°C below oil smoke point.
- Bulb thermostats immersed in oil are more efficient in sensing the temperature inside the tank, promptly adjusting the oil to the desired temperature, minimising smoke points, and prolonging the oil life.
- A safety thermostat triggers in case of abnormal operation.
- Green light indicating voltage presence.
- Orange light indicating that the heating elements are heating up.
- Technical compartment for easy connection to the electrical network.

TECHNICAL DATA

TOTAL POWER	14 kW	ELECTRIC POWER	14 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
TEMPERATURE RANGE	100÷190 °C	TANK CAPACITY	8lt+8lt
TANK DIMENSIONS	14x34,2x25,7 cm	HEATING	Rotating heating elements in the tank
MINIMUM POWER CABLE CROSS-SECTION	5 x 2,5 n° - mm ²	ELECTRIC CABLE TYPE	H07 RN-F
TANK TYPE	AISI 304	TANKS	n° 2
ELECTRICAL CONNECTION HEIGHT (H)	0 mm	ELECTRICAL CONNECTION HEIGHT (X)	374 mm
ELECTRICAL CONNECTION HEIGHT (Y)	-472 mm	FOOT HEIGHT	155 mm
FOOT ADJUSTMENT	155/250 mm	IPX RATING	4
WIDTH	40 cm	DEPTH	70 cm
HEIGHT	90 cm	PACKAGE WIDTH	81,0 cm
PACKAGE DEPTH	47,0 cm	PACKAGE HEIGHT	114,0 cm
NET WEIGHT	46,2000 kg	GROSS WEIGHT	56,4 kg
VOLUME	0,4300 m ³	HARMONISED CODE	84198180
LATENT HEAT RELEASE	9800.0 W	SENSIBLE HEAT RELEASE	1260.0 W
STEAM RELEASE	14420.0 g/h		

ACCESSORIES

220650	2 EXTRA FRYER BASKETS (8+8/13/14L) - DIM. CM (10.5X29.5X12H)
719004	TECNO74 REAR COVERING PANEL FOR FREESTANDING ELEMENTS (L=40CM)
799503	SIDE COVERING PANEL FOR FREESTANDING MODULE
799506	PAIR OF CLOSING ELEMENTS (L=70CM)
799507	EXTRA OIL-RECOVERY TANK FOR FRYERS (8+8L, 13L, 17L)

INSTALLATION SCHEMES

