
716102

PCU8FE7

FREESTANDING ELECTRIC BOILING TOP WITH 4 SQUARED COPLANAR TILTING PLATES (30X30 CM - 11.8X11.8 IN) ON OPEN CABINET



- Freestanding boiling top with 4 coplanar, tilting, electric plates on an open cabinet (80 cm).
- Coplanar, tilting, squared, cast iron electric plates (30x30 cm and 8 mm thick) not hermetically sealed to the worktop.
- 3 kW power for each plate adjustable to 6 levels.
- Temperature limiter inside the plates to reduce energy consumption.
- Heating and control commands specific for each plate.
- Lights warning when the plates are on.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to facilitate connection to the electrical network.

TECHNICAL DATA

TOTAL POWER	12 kW	ELECTRIC POWER	12 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
BOILING TOP POWER	12 kW	COOKING ZONE POWER	4X3 n°- kW
ELECTRIC PLATE DIMENSIONS	30x30 cm	CABINET DIMENSIONS	73x57,4x39,5 cm
NUMBER OF COOKING ZONES	n° 4	MINIMUM POWER CABLE CROSS-SECTION	5 x 2,5 n° - mm ²
ELECTRIC CABLE TYPE	H07 RN-F	ELECTRICAL CONNECTION HEIGHT (Y)	-63 mm
FOOT HEIGHT	155 mm	FOOT ADJUSTMENT	155/250 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	70 cm	HEIGHT	90 cm
PACKAGE WIDTH	96 cm	PACKAGE DEPTH	81 cm
PACKAGE HEIGHT	114,0 cm	NET WEIGHT	100 kg
GROSS WEIGHT	113 kg	VOLUME	0,79 m ³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	960.0 W
SENSIBLE HEAT RELEASE	2400.0 W	STEAM RELEASE	1416.0 g/h

ACCESSORIES

- 319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
- 719005 TECNO74 REAR COVERING PANEL FOR FREESTANDING ELEMENTS (L=80CM)
- 799503 SIDE COVERING PANEL FOR FREESTANDING MODULE
- 799506 PAIR OF CLOSING ELEMENTS (L=70CM)

INSTALLATION SCHEMES




Fig.1 | Abb.1 | рис.1 - 5415.648.00