
716130
CPD4FE7
GN2/3 FREESTANDING SINGLE TANK 24L ELECTRIC PASTA COOKER WITH ELECTRONIC CONTROL ON CLOSED CABINET - BASKETS NOT INCLUDED



- Freestanding GN2/3 electric pasta cooker 24 L with electronic control on a closed cabinet (40 cm).
- Power: 6.0 kW.
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Pasta cookers are also to boil rice, vegetables, meat and other products.
- The electronic control allows for greater precision between the set temperature and the tank temperature. It also enables vacuum cooking from 50 to 75°C.
- Cooking programmes can be saved, thus creating standardised recipes.
- Deep drawn worktop with a seamlessly welded deep drawn cooking tank, featuring rounded corners, overflow-proof tank and large foam expansion area.
- AISI 316 stainless steel tank, drainpipe, and false bottom for long-lasting resistance against salt corrosion.
- Water filling control inside the cabinet.
- Heating through armoured heating elements in Incoloy alloy outside the cooking tank to facilitate cleaning and enhance durability.
- Safety thermostat to protect the tank against ignition without water or excessive evaporation.
- Water dispenser on the rear of the worktop.
- Overflow for draining starch in the front part of the tank.
- Bottom drain.
- Technical compartment for easy connection to the electrical network.
- Baskets not included.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).

TECHNICAL DATA

TOTAL POWER	6 kW	ELECTRIC POWER	6 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
TANK CAPACITY	24lt	LOADING WATER	Water inlet on the worktop
TANK DIMENSIONS	30,5x34,1x30,3 cm	MINIMUM POWER CABLE CROSS-SECTION	5 x 1,5 n° - mm ²
ELECTRIC CABLE TYPE	H07 RN-F	TANK TYPE	AISI 316
WATER CONNECTION POSITION	Bottom	WATER DRAIN POSITION	Bottom
ELECTRICAL CONNECTION HEIGHT (Y)	-471 mm	GAS CONNECTION DIAMETER	1/2"G EN10226-1
WATER CONNECTION DIAMETER	1/2"	DRAIN DIAMETER	1"
DRAIN CONNECTION HEIGHT (H)	0 mm	DRAIN CONNECTION HEIGHT (X)	145 mm
DRAIN CONNECTION HEIGHT (Y)	-365 mm	FOOT HEIGHT	155 mm
FOOT ADJUSTMENT	155/250 mm	IPX RATING	4
WIDTH	40 cm	DEPTH	70 cm
HEIGHT	90 cm	PACKAGE WIDTH	81 cm
PACKAGE DEPTH	47 cm	PACKAGE HEIGHT	114 cm
NET WEIGHT	39 kg	GROSS WEIGHT	51 kg
VOLUME	0,43 m ³	HARMONISED CODE	84198180
LATENT HEAT RELEASE	1200.0 W	SENSIBLE HEAT RELEASE	210.0 W
STEAM RELEASE	1764.0 g/h		

ACCESSORIES

120620	PASTA COOKER BASKETS (2 X GN1/3) - DIM. CM (29X16X20H)
120625	PASTA COOKER BASKET (4 X GN1/6) - DIM. CM (14X14X20H)
120635	PASTA COOKER BASKET (1 X GN2/3) - DIM. CM (29X29X20H)
120652	PASTA COOKER LID (GN2/3)
120660	PASTA COOKER BASKET (1 X GN1/3 + 2 X GN1/6) - DIM. CM (29X16X20H) (14X14X20H)
120700	PASTA COOKER BASKET (2 X GN2/6) - DIM. CM (14.5X29X20H)
719004	TECNO74 REAR COVERING PANEL FOR FREESTANDING ELEMENTS (L=40CM)
799503	SIDE COVERING PANEL FOR FREESTANDING MODULE
799506	PAIR OF CLOSING ELEMENTS (L=70CM)

INSTALLATION SCHEMES

