

716171

GD8E7N

ELECTRIC CONTACT GRILL WITH WATER (TOP VERSION)



- Electric water grill with direct cooking on heating elements (80 cm), top version.
- Power: 2x4.1 kW.
- 2 independent cooking zones.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- AISI304 stainless steel tank seamlessly welded to the AISI 304 stainless steel top with Scotch Brite finish.
- Tilting armoured heating elements with an oval profile for direct cooking. They are made of AISI 304L stainless steel with low carbon content to ensure excellent resistance to corrosion. Moreover, they comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- Safety micro switch in the raised position of the heating elements.
- Automatic water filling with solenoid valve and reducer with a 0.1 l/min capacity.
- Water drain in the centre of the tank with 1 ½ inch pipe. Regulation of the water level in the tank through a removable and washable overflow.
- Equipped with a wire mesh filter, the overflow prevents larger food residues from obstructing the drain and makes it easier to clean the tank.
- Operating thermostat with automatic reset serving as an empty tank safety device.
- Red light on the control panel indicating empty tank.
- Green light indicating voltage presence.
- Orange light indicating that the heating elements are heating up.
- Energy regulator 0-6-INFINITE which simultaneously activates the heating element and tank water filling. Maximum temperature 400°C.
- Removable splashback on 3 sides included.
- A stainless steel scraper shaped is included as per standard. It is shaped as the heating element profile to facilitate cleaning, and it can also be used to lift the heating element unit.
- Plastic elbow fitting for rear draining, designed for high-temperature use, included.
- The electric components, such as solenoid valves and contactors, are positioned near the control panel to facilitate maintenance.
- Technical compartment for easy connection to the electrical network.

TECHNICAL DATA

TOTAL POWER	8,2 kW	ELECTRIC POWER	8,2 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
LOADING WATER	Injector in the tank	NUMBER OF COOKING ZONES	n° 2
HEATING	Direct	MINIMUM POWER CABLE CROSS-SECTION	5 x 2,5 n° - mm ²
COOKING SURFACE	54,5x44,7 cm	ELECTRIC CABLE TYPE	H07 RN-F
HEATING ZONES	n° 2	WATER CONNECTION POSITION	4,7cm
WATER DRAIN POSITION	6cm	ELECTRICAL CONNECTION HEIGHT (H)	32 mm
ELECTRICAL CONNECTION HEIGHT (X)	721 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-62 mm
WATER CONNECTION DIAMETER	3/4"	WATER CONNECTION HEIGHT (H)	32 mm
WATER CONNECTION HEIGHT (X)	48 mm	WATER CONNECTION HEIGHT (Y)	-62 mm
DRAIN DIAMETER	1" 1/2	DRAIN CONNECTION HEIGHT (H)	45 mm
DRAIN CONNECTION HEIGHT (X)	400 mm	DRAIN CONNECTION HEIGHT (Y)	-62 mm
FOOT HEIGHT	15 mm	FOOT ADJUSTMENT	15/25 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	70 cm	HEIGHT	28 cm
PACKAGE WIDTH	88 cm	PACKAGE DEPTH	82 cm
PACKAGE HEIGHT	55 cm	NET WEIGHT	41 kg
GROSS WEIGHT	51,6 kg	VOLUME	0,39 m ³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	1435.0 W
SENSIBLE HEAT RELEASE	6560.0 W	STEAM RELEASE	2107.4 g/h

ACCESSORIES

- 719040 SIDE HEAT PROTECTION DEVICE
 799506 PAIR OF CLOSING ELEMENTS (L=70CM)

INSTALLATION SCHEMES

