


716188

PPF8E7

## ELECTRIC SOLID TOP ON GN2/1 ELECTRIC STATIC OVEN WITH 1 GRID





- Electric solid top cooker (80 cm) with 4 independent zones on a GN 2/1 electric static oven.
- Electric solid tops and cookers are suitable for indirect cooking only.
- Overflow-proof worktop with raised and welded edges.
- Non-deformable, molybdenum steel plate (15 mm thick) with prolonged heat retention properties.
- Ultra-fast radiant heating elements secured under the 2.0 kW plate for each independent area.
- Ultra-rapid infrared heating elements secured under the plate with a power of 2.0 kW for each independent zone.
- Maximum temperature of 470°C.
- Energy regulator 0-6-infinite.
- Temperature limiter inside the plates to reduce energy consumption.
- Heating and control commands specific for each zone.
- Safety thermostat.
- Lights warning when the heating zones are active.
- Setup for installing a water tap.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).

## >> GN 2/1 ELECTRIC STATIC OVEN

- >> AISI 304 stainless steel oven door.
- >> Stainless steel cooking chamber and long-lasting steel mesh and glass fibre gasket resistant to high temperatures.
- >> Heating through upper and lower heating elements that can be activated together or separately.
  - >> Thermostatic control 60-270°C.
  - >> Stainless steel removable side tray racks.
  - >> 1 grid supplied.
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to facilitate connection to the electrical network.



TECHNICAL DATA			
TOTAL POWER	13,3 kW	ELECTRIC POWER	13,3 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
OVEN POWER	5,3 kW	BOILING TOP POWER	8 kW
COOKING ZONE POWER	4x2 n°- kW	TRAY CAPACITY	n° 4xGN2/1
COOKING CHAMBER DIMENSIONS	57,5x65x30 cm	OVEN DIMENSIONS	GN2/1
ELECTRIC PLATE DIMENSIONS	76,3x58 cm	GUIDES	n° 4
NUMBER OF COOKING ZONES	n° 4	VERTICAL DISTANCE BETWEEN TRAYS	6 cm
OVEN TEMPERATURE RANGE	60÷270 °C	MINIMUM POWER CABLE CROSS-SECTION	5 x 2,5 n° - mm²
ELECTRIC CABLE TYPE	H07 RN-F	OVEN TYPE	Static
PLATE TYPE	Iron and molybdenum	HEATING ZONES	n° 4
ELECTRICAL CONNECTION HEIGHT (H)	0 mm	ELECTRICAL CONNECTION HEIGHT (X)	650 mm
ELECTRICAL CONNECTION HEIGHT (Y)	-580 mm	FOOT HEIGHT	155 mm
FOOT ADJUSTMENT	155/250 mm	IPX RATING	4
WIDTH	80 cm	DEPTH	70 cm
HEIGHT	90 cm	PACKAGE WIDTH	85,0 cm
PACKAGE DEPTH	82,0 cm	PACKAGE HEIGHT	114,0 cm
NET WEIGHT	130,5000 kg	GROSS WEIGHT	148,0000 kg
VOLUME	0,7900 m³	HARMONISED CODE	84198180

## **ACCESSORIES**

220590 EXTRA OVEN GRID GN2/1 (53X63CM)

619012 GN2/1 INOX TRAY

799506 PAIR OF CLOSING ELEMENTS (L=70CM)



## **INSTALLATION SCHEMES**

