

716241

FTLD8FE7

FREESTANDING ELECTRIC GRIDDLE WITH 1/3 RIBBED PLATE AND ELECTRONIC CONTROL ON OPEN CABINET



- Freestanding electric griddle on an open cabinet (80 cm) with electronic control and a 2/3 smooth and 1/3 ribbed steel cooking plate.
- 2 independent cooking zones.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- The electronic control allows for greater precision between the set temperature and the cooking plate temperature.
- Cooking programmes can be saved, thus creating standardised recipes.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Sloped cooking plate (12 mm thick) to facilitate the drainage of grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Heating through stainless steel armoured heating elements.
- \bullet Operating thermostatic valve with a switch and temperature control ranging between 70°C and 310°C.
- Fitted with a safety thermostat that triggers in case of abnormal operation.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the electrical network mains.



TE(CH	NI	CA	LE)A ⁻	ГΑ

TOTAL POWER	7,8 kW	ELECTRIC POWER	7,8 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
TEMPERATURE RANGE	60÷270 °C	CABINET DIMENSIONS	73x57,4x39,5 cm
MINIMUM POWER CABLE CROSS-SECTION	5 x 1,5 n° - mm²	COOKING SURFACE	74,8x56,4 cm
ELECTRIC CABLE TYPE	H07 RN-F	PLATE TYPE	1/3 ribbed and 2/3 smooth
HEATING ZONES	n° 2	ELECTRICAL CONNECTION HEIGHT (H)	660 mm
ELECTRICAL CONNECTION HEIGHT (X)	721 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-63 mm
FOOT HEIGHT	155 mm	FOOT ADJUSTMENT	155/250 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	70 cm	HEIGHT	90 cm
PACKAGE WIDTH	85 cm	PACKAGE DEPTH	82 cm
PACKAGE HEIGHT	114 cm	NET WEIGHT	86,5 kg
GROSS WEIGHT	104 kg	VOLUME	0,79 m³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	3120.0 W
SENSIBLE HEAT RELEASE	2574.0 W	STEAM RELEASE	4586.4 g/h

ACCESSORIES

120597 SCRAPER - SPARE BLADE KIT (10 PCS)

319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90

719005 TECNO74 REAR COVERING PANEL FOR FREESTANDING ELEMENTS (L=80CM)

719040 SIDE HEAT PROTECTION DEVICE

799503 SIDE COVERING PANEL FOR FREESTANDING MODULE

799506 PAIR OF CLOSING ELEMENTS (L=70CM)



INSTALLATION SCHEMES



IMMAGINE DA DEFINIRE