
716250

FTRD12BFE7

**FREESTANDING ELECTRIC GRIDDLE WITH
BRUSHED, CHROME-PLATED, 1/3 RIBBED PLATE
ON OPEN CABINET**



- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- The electronic control allows for greater precision between the set temperature and the cooking plate temperature.
- Cooking programmes can be saved, thus creating standardised recipes.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Sloped cooking plate (12 mm thick) to facilitate the drainage of grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with a switch and temperature control ranging between 70°C and 310°C.
- Fitted with a safety thermostat that triggers in case of abnormal operation.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the electrical network mains.

TECHNICAL DATA

TOTAL POWER	11,7 kW	ELECTRIC POWER	11,7 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
TEMPERATURE RANGE	60÷270 °C	CABINET DIMENSIONS	113x57,4x39,5 cm
MINIMUM POWER CABLE CROSS-SECTION	5 x 2,5 n° - mm ²	COOKING SURFACE	113x56 cm
ELECTRIC CABLE TYPE	H07 RN-F	PLATE TYPE	Brushed chrome-plated - 1/3 ribbed and 2/3 smooth
HEATING ZONES	n° 3	ELECTRICAL CONNECTION HEIGHT (H)	660 mm
ELECTRICAL CONNECTION HEIGHT (X)	1121 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-63 mm
FOOT HEIGHT	155 mm	FOOT ADJUSTMENT	155/250 mm
IPX RATING	4	WIDTH	120 cm
DEPTH	70 cm	HEIGHT	90 cm
PACKAGE WIDTH	125 cm	PACKAGE DEPTH	82 cm
PACKAGE HEIGHT	112 cm	NET WEIGHT	137 kg
GROSS WEIGHT	150 kg	VOLUME	1,13 m ³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	4680.0 W
SENSIBLE HEAT RELEASE	3861.0 W	STEAM RELEASE	6879.6 g/h

ACCESSORIES

120595	GRIDDLE-CLEANING SCRAPER
120597	SCRAPER - SPARE BLADE KIT (10 PCS)
719040	SIDE HEAT PROTECTION DEVICE
799506	PAIR OF CLOSING ELEMENTS (L=70CM)

INSTALLATION SCHEMES



IMMAGINE DA DEFINIRE